ACCESS + VISTA INTEGRATION

VISTA 128FBP/ 250FBP FEATURES



Access + VISTA integration is Honeywell's most comprehensive access control platform. Combining an easy-to-use access control system with video and intrusion into a single interface, Access + VISTA integration offers a complete security management solution including access control, alarm monitoring,

video badging and CCTV system. Access + VISTA integration is the next generation of the Pro-Watch and WIN-PAK platforms. It provides a three-in-one solution that offers end users substantial enhancements to existing systems or significantly improves the operation of new security systems by reducing training and labour.

VISTA-128FBP

Combination Fire/Burglary Control Panel

Features

- Capacity:
- Zones: 8-128 - Event Log: 512
- Partitions: 8 - Users: 128
- Two Expansion Methods:
- V-Plex polling loop (two-wire)
- UL Commercial Wireless
- User Interfaces:
- 6160CR Custom Alpha Display (Fire) / 6271CV Touch Screen
- All VISTA-128FBP features plus: - UL Commercial Fire Wireless
- (2) Two-wire smoke loops on board with optional expansion
- PID smoke detector compatible
- On-board reset for four-wire smoke
- Two on-board notification appliance circuits (NAC)
- Automatic smoke detector sensitivity maintenance testing

Distributed by:

www.asia.security.honeywell.com

Honeywell Security & Data Collection Asia Pacific

Automation & Control Solutions Honeywell International Inc. www.securiity.honeywell.com

Jan 2009

VISTA-250FBP

Combination Fire/Burglary Control Panel

Features

- Capacity: - Zones: 8-250
- Event Log: 1000
- Partitions: 8 - Users: 250
- Two Expansion Methods:
- V-Plex Polling Loop (two-wire)
- UL Commercial Wireless
- User Interfaces:
- 6160CR Custom Alpha Display (Fire) / 6271CV Touch Screen
- All Vista-250FBP features plus:
- UL Commercial Fire Wireless
- (2) Two-wire smoke loops on board with optional expansion
- PID smoke detector compatible
- On-hoard reset for four-wire smoke
- Two on-board notification appliance circuits (NAC)
- Automatic smoke detector sensitivity maintenance testing

ALSO AVAILABLE:

V128FBP-24, 24V version / V250FBP-24, 24V version

Compatible devices:

- 5800CO Wireless Carbon Monoxide detector (coming soon)
- 4204CF Commercial Fire Relay
- 4208SNF Eight-Zone Expander (Class A or B)
- 5192SD and 5192SDT V-Plex Polling Loop Smoke Detectors





Honeywell

VISTA SERIES



The Vista family is a series of totally compatible control panels designed to support the easiest to use end-user interfaces available. Vista offers more flexibility & simpler programming along with features that customers want. As the world's largest manufacturer of electronic security products, Honeywell builds proven performance into everything we make. Combine this with the 5800 Series wireless transmitters, and you now have the most flexible, reliable and cost effective solutions for security and home/business control.

A blend of head turning style and sophisticated technology, the state of the art touchscreen keypad makes security system operation easier then ever – with graphics and simple prompts guiding you every step of the way. By just touching the graphics on the intuitive, easy to read touchscreen display, you can conduct a variety of everyday tasks with unprecedented ease.

Our products do more than keep you safe...they can improve household communication, make your home more comfortable and provide a level of simplicity and convenience you'll really appreciate. Best of all, they can enhance the quality of life.

With solid features and robust system capacities, you'll find Vista panels to be the ideal choice for all your installations.











BURGLARY

VISTA-10P / 20P FEATURES

	VISTA-10P	VISTA-20P
System Capacity	00	40
Maximum Zone Capacity	22	48
Std. Hardwired Zones (w/zone doubling)	6 (-)	8 (15)
Maximum Hardwired Expansion	0	40
Maximum Wireless Expansion	16	40
Wireless Keys (do not use zones)	8	16
Partitions	1	2"true"
User Codes	16	48
Event Log	32	100
Max. Expansion of 2-Wire Smokes	0	16
Maximum Number of Schedules	2	32
False Alarm Prevention Features		
Exit Error Logic	\checkmark	\checkmark
Exit Delay Reset	V	
Exit Delay Countdown	V	V
Cross Zoning	V	· √
Alarm Verification - Fire	√ √	, √
Swinger Shutdown	√	√ √
Unvacated Auto-Stay	√	1
Alarm Cancel Verification	√	v
Alarm Cancel verification	٧	٧
System Configuration	1	1
Interactive Phone Support	V	V
Real Time Clock	$\sqrt{}$	V
Temporal Bell	V	V
Bell Supervision	$\sqrt{}$	$\sqrt{}$
Telephone Line Monitor	_	$\sqrt{}$
On-Board Triggers	2	2
Relays Supported	4	16
X-10 Devices Supported	_	16
Additional Features		
Master Console	N/A	_
Cross Partitioning (goto)	_	V
"Night" Arming		
RF Supervision by Transmitter	√ √	√ √
	v N/A	V
Common Lobby Logic	,	V al
Configurable Zone Type	V	V I
"Battery Saver"	V	V
Keyswitch Arming	V	V
Access Schedules	V	V
Output Device Schedules	V	V
Convenience Features		,
Single Button Arming	V	√
Quick Exit	$\sqrt{}$	$\sqrt{}$
Keypad Macros	V	V
Viewable Event Log at Keypad	V	V
viewabie Everit Eog at Neypau	V	
	V	V
Time & Date Display	V	√ 4
		√ 4 √

 $[\]sqrt{\text{(Supported Feature)}}$ – (Not Supported) N/A (Not Applicable)

COMMERCIAL BURGLARY

VISTA-120 / 250BP FEATURES

	VISTA-120	VISTA-250BP
System Capacity		
Max. Zones	128	250
HW Standard	9	9
HW Exp	119	241
5800 Zones	128	249
Keyfob Zones	-	-
Users	150	250
Event Log	512	1000
Two-wire Smokes	16 (zone 1)	16 (zone 1)
our-wire Smokes	Zones 1-8	Zones 1-8
Max. No. of Keypads	31 address device	31 address device
Max. No. 4204	15	15
Max. No. 4219 / 4229	-	-
False Alarm Prevention Features		
Swinger Shutdown	1-15 alarms	1-15 alarms
Auto Stay	-	V
Cross Zoning	$\sqrt{}$	V
Exit Alarm	√	V
Quick Exit/Exit Restaurant		V
Exit Delay Reset	V	V
System Configuration		
Keyswitch	$\sqrt{}$	$\sqrt{}$
Outputs	96	96
Aux Power	12v 750mA	12v 1 amp
Alarm Power	1.7 amps	1.7 amps
Additional Features		
Partitions	8	8
Line Fault	ν V	J
Access Control	Relays/VGM/VISAKEY	Relays/VGM/VISAKEY
4285/4286	\(\sqrt{101ay5/Valvi/V10/11\(\text{L}\)}	√ VION (NET
4AV	Eagle	Eagle
Vent Zone		
Custom Words	60	60
Jp & About		
Panel Linking	V	
Night Stay Mode		· · · · · · · · · · · · · · · · · · ·
Chime by Zone		-
Dynamic Signaling	√	
Dyriai ilic Sigi iaiii ig	V	٧
Convenience Features	-1	ا
Graphic Support	√ 110	V
V-Plex	119	241
Zone Doubling	-	-
Single-Button Arming	-	-
Schedules	20	20
Programmable Zone Types	-	-
Keypad Macros	32	32
Pager	<u>-</u>	V

 $[\]sqrt{\text{(Supported Feature)}}$ – (Not Supported) N/A (Not Applicable)