

# 968XTP

HIGH SECURITY SWITCH



The 968XTP High Security Magnetic Switch is intended to monitor the open or closed position of moveable assemblies such as doors, windows or machinery safety barriers, where an attempt to defeat the switch is a concern.

The 968XTP High Security Contact provides maximum security for protection of safes, vaults and other high security applications.

Utilizing balanced magnetic contacts, the 968XTP is highly defeat resistant. In addition, internal circuitry provides 2400VDC of surge protection.

## FEATURES

- Defeat-resistant from external magnetic tampering
- Includes tamper switch to notify of removal
- Uses industry standard mounting dimensions
- Suitable for Indoor/Outdoor use
- Epoxy sealed for protection from moisture and corrosion
- 3 ft stainless steel armored cable
- UL/cULus Listed

## SPECIFICATIONS

- **Switch Type**  
Form C (SPDT)
- **Contact Rating**  
25mA @ 24VDC  
3 ft Stainless Steel Armored Cable
- **Tamper Rating**  
1 Amp @ 24VDC
- **Gap**  
7/16 inches (11mm)
- **Surge Protection**  
Up to 2400VDC

## ORDERING

**968XTP** High Security Switch

**Honeywell Security & Custom Electronics**  
Honeywell  
2 Corporate Drive  
Melville, NY 11747  
www.honeywell.com

# Honeywell

L/968XTP/D  
April 2007  
© 2007 Honeywell International Inc.